

RAM FLAT® Compactors allow their users to significantly reduce their costs to dispose of hazardous and radioactive waste. This is done by reducing the volume of the waste by compacting the material right into the drum.

Only interested in crushing empty drums? No problem. Some of the *RAM FLAT Compactor* models are designed specifically to crush empty drums into metal pancakes. But the real bonus is the ability to configure one *RAM FLAT Compactor* to both crush empties and to compact waste into drums.

RAM FLAT MEANS QUALITY

For over twenty-five years we have designed *RAM FLAT Compactors* around these quality parameters:

- Top Quality, USA made electrical, hydraulic & pneumatic componentry
- Easy to use controls: Down, Up & Emergency Stop. Bottom Stop optional
- Adjustable compaction Pressure
- Completely enclosed crushing chamber
- Interlocked safety chamber door for operator safety
- Unitized, welded-body construction
- Liquid tight electrical conduit, all steel hydraulic tubing
- Oil-tight 115v push button controls
- Large oil reservoir for efficient cooling of the hydraulic circuit and seal protection

FLEXIBLE DESIGN

With field proven experience in compacting materials like paint filters, radioactive lab waste and even simple product destruction, the *RAM FLAT Compactor* has the ability to be customized to meet your application. Some of the customized options we have designed include:

- Multiple drum sizes with single machine
- Bolt on Crushing Plate for drum crushing
- Remote location machine controls
- Programmable machine controls
- Ergonomic sensitive drum handling system
- Drum piercing & drainage
- Provisions for outside installations
- Air Filtration (particulate & vapor)
- Liquid removal from the compacted waste
- Waste spring back management
- Non-sparking surfaces
- Stainless Steel construction

HAZARDOUS LOCATIONS

For explosion-proof locations, we offer two unique control designs which reduce the need for bulky and expensive electrical fittings and enclosures:

- Hydraulic Controls: electric controls and interlocks are replaced with non-sparking hydraulic control logic
- Pneumatic Controls: electric controls and interlocks are replaced with non-sparking pneumatic control logic

Standard explosion-proof designs feature a Class 1, Div. 1, Group D electrical motor.



S & G Enterprises, Inc.

N 115 W 19000 Edison Dr.
Germantown, WI 53022

Tel: (262) 251-8300 (800) 233-3721

Fax: (262) 251-1616

www.ramflat.com

55A, 55AR & 85AR

Built for continuous duty & demanding applications

- **85,000 lbs. hydraulic force** for inside drum compaction/ drum crushing
- 55AR & 85AR have extra large drum clearance for material overflow
- 85AR= up to 85 gal. drums / 55A & 55AR= 55 gal. drums
- 6" cylinder with 5" chrome rod
- Lateral support rods minimizes piston rod stress
- .375 Steel Plate Crushing Chamber with 1.5" thick base plate
- 1" Steel Compaction Head with reinforcing gussets
- Positive Displacement Piston Pump for consistent cylinder travel speed

55
AR



Model	55A		55AR		85AR	
Compaction Chamber Height	38.5"	97.8cm	50.5"	128.3cm	50.5"	128.3cm
Compaction Chamber Width	32.5"	82.6cm	32.5"	82.6cm	36"	91.4cm
Door Opening Width	27"	68.6cm	27"	68.6cm	29"	73.7cm
Full Cycle Time	65 sec.		81 sec		81 sec	
Machine Depth	39"	99.1cm	39"	99.1cm	43"	109.2cm
Machine Width	36"	91.4cm	36"	91.4cm	40"	101.6cm
Overall Machine Height	106.25"	270.0cm	130.25"	331.0cm	130.25"	331.0cm
Electric Motor	10 HP	7.5kW	10 HP	7.5kW	10 HP	7.5kW
Ship Weight Including Oil	3525 Lb.	1600 kg	3870 Lb.	1755 kg	4170 Lb.	1892 kg